



Service Bulletin

Bulletin No. 2016-68
OEM No. 2016-68

Circulate to: Sales Manager Accounting Service Manager Technician Parts Manager

Mercury Diesel Joystick Piloting System Changes

Models Affected

Models Covered	Serial Number Or Year
Mercury Diesel 4.2 V8 TDI sterndrive models (Tier 3)	All
Mercury Diesel 3.0 V6 TDI sterndrive models (Tier 3)	All

Scope

Worldwide

Situation

The intention of this bulletin is to inform dealers and OEM's of the following new components along with a brief description of how they look and function.

The following new Joystick components are explained in this bulletin along with Mercury Diesel with Joystick Piloting for Sterndrive products. For detailed instructions on installations and functions, refer to the appropriate installation manual.

- Helm sensor assembly
- Global positioning system (GPS)/inertial measurement unit (IMU)
- Joystick
- New helm harness changes
- VesselView Link
- VesselView 502
- VesselView 702
- Operational features
- Rigging kit table
- Auxiliary Joystick table
- Current production engine model table
- Service engine model table


THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

Helm Sensor Assembly

Helm Sensor Assembly Overview

The following illustration covers the electrical connections of the unit:



Helm sensor assembly connections

- a** - Helm sensor assembly
- b** - Helm sensor assembly CAN P (blue) connection
- c** - Helm harness CAN P (blue) connection
- d** - Helm harness CAN H (orange) connection
- e** - Helm sensor assembly CAN H (orange) connection

The following items are a few key points of the helm sensor assembly.

- Each helm must have a helm sensor assembly.
- The helm sensor assembly is fully redundant between the port and starboard systems.
- The helm sensor assembly provides resistive end stops.
- The maximum drop length is 7 m (23 ft).

GPS/IMU

GPS/IMU Overview

The GPS antenna and IMU have been combined into one unit yet the individual features have not changed.

The following information covers the mounting recommendations, functionality, and calibration of the GPS/IMU:




GPS/IMU

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

Mounting Recommendations

The illustration and table highlights the desired mounting location.



Location	Location description
1	This location (above the deck) provides optimal GPS performance.
2	This location (inside the boat) may obstruct the GPS performance.
3	This location (inside the boat) is not recommended for GPS installation.

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

Functionality

The light on the top of the GPS/IMU indicates the status of the unit while it is powered up. Refer to the following table for more information:



LED Color	LED Code	Status	Action Required
<p>60814</p>	Green light—1 blink every 15 seconds.	Normal operation	None
<p>60815</p>	Green light—1 flash every 0.5 second.	Unit is initializing and is in a Not Ready status.	None—normal power up takes <1 minute.
<p>60816</p>	Green light—1 flash every 1 second.	GPS sensor is initializing and is in a Not Ready status.	None—typically lasts 3–5 minutes out of the box, after factory reset, or software update.
<p>60817</p>	Green light—1 flash every 2 seconds.	Compass linearizing	None—normal operation.
<p>60818</p>	Red light—1 flash every 3 seconds.	Internal fault/error, GPS No signal.	Confirm unit has clear view of sky and unit isn't damaged. If so, contact Mercury Marine Technical Support.
<p>61029</p>	Red light—2 flashes every 4 seconds.	No CAN bus detected.	Check all wiring connections. Then contact Mercury Marine Technical Support.
<p>61028</p>	Red light—7 flashes every 9 seconds.	Power and CAN bus detected but no transfer or receive (TX/RX).	Contact Mercury Marine Technical Support.

Calibration

Calibration of the GPS/IMU is not required. To program a Heading offset, use CDS G3.

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

Joystick

Joystick Overview

The following photos illustrate the visual differences between the two designs of the joystick.

NOTE: The initial production of the joystick will have the external noise suppressor in-line and will be short-term. Long-term production of the joystick will have the noise suppressor incorporated inside the joystick. Either joystick can be used, the functionality remains the same between the two designs of the joystick.

This photo depicts the joystick with an external noise suppressor.



Joystick with external noise suppressor

This photo depicts the joystick with an internal noise suppressor.




Joystick with internal noise suppressor

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

The following illustration and table gives an overview of how the joystick functions:



Ref	Description	Notes
a	Light ring	The light ring will illuminate, flash, pulse, or rotate, to indicate a large variety of states. Refer to the individual operation for specifics. The light ring will flash when an input error occurs.
b	Heading mode course adjustment indicators and textual indicator	The course adjustment indicators illuminate when the system is in auto heading mode. They remind the operator that: <ul style="list-style-type: none"> Twisting the joystick to the right will change the heading by 10° starboard Twisting the joystick to the left will change the heading by 10° port Bumping the joystick to the right will change the heading by 1° starboard Bumping the joystick to the left will change the heading by 1° port The textual indicator illuminates whenever the auto heading mode is engaged.
c	Skyhook mode indicators	Both the textual indicator SKYHOOK and the Skyhook icon illuminate when Skyhook mode is engaged.
d	Route textual indicator	Illuminates when the route (waypoint sequencing) mode is engaged.
Trackpad Lights		
e	Heading button light	Illuminates when the auto heading mode is engaged.
f	Skyhook button light	Illuminates when Skyhook is engaged.
g	Route (waypoint sequencing) button light	Illuminates when the route (waypoint sequencing) mode is engaged.
h	Adjust button lights	These two light segments illuminate to indicate the degree of fine-tuning applied to each function. Refer to the individual function description for details.


New Helm Harness Changes

Previous Mercury Marine Joystick products (Zeus, Axius, and JPO—design I) required an external power and ground at the helm harness. This was accomplished by connecting the main power relay harness to the **STBD POWER DISCONNECT** connector on the helm harness. Refer to callout **b** in the following illustration.

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

Current Mercury Marine Joystick products (JPO—design II, JPS, and Zeus Joystick Piloting) no longer require a main power relay harness to be connected to the helm harness. The **STBD POWER DISCONNECT** connector must remain connected. Refer to callout **b** in the following illustration.



Dual-engine helm harness, helm panel end

- a** - CAN P—also known as CAN 1 connectors
- b** - STBD POWER DISCONNECT
- c** - Starboard switched load
- d** - OEM Skyhook—under tag
- e** - Starboard tachometer link
- f** - Port tachometer link
- g** - Port switched load
- h** - CAN H—also known as CAN 3 connectors
- i** - CAN H link—for triple-engine and quad-engine applications
- j** - CAN P link—for triple-engine and quad-engine applications

61939

VesselView Link


VesselView Link Overview

The VesselView Link allows the joystick piloting system to communicate with NMEA 2000 components, such as an approved multifunction display (MFD) or chartplotter.

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

IMPORTANT: The VesselView Link can be used in a single or multiengine application. For Mercury Diesel applications, the multiengine VesselView Link must be ordered. Ensure you choose the correct part number since the part numbers are different between the single and multiengine application.



VesselView Link

- a** - VesselView Link (SmartCraft) connector
- b** - NMEA 2000 connector

VesselView 502

VesselView 502 Overview

The following information covers some key features of the VesselView 502:

- Touchscreen with no buttons
- VesselView Link module required
- Mounting options:
 - Flush mount
 - Surface mount
- Internal Wi-Fi
- Internal bluetooth
- Internal GPS (10 Hz)
- Broadband sonar with built-in compressed high-intensity radiated pulse (CHIRP)

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

- Full featured chartplotter



61269


VesselView 502

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

VesselView 502 Connections

The following diagram is an example of how the VesselView 502 could be installed.



60876

Typical NMEA communication connection

- a- Chartplotter or multifunction display
- b- 120 ohm termination resistor, male
- c- 120 ohm termination resistor, female
- d- NMEA 2000 fused power source
- e- Power bus
- f- VesselView 502
- g- VesselView 502 harness
- h- VesselView Link controller
- i- VesselView Link harness
- j- Junction box

VesselView 702

VesselView 702 Overview

The following information covers some key features of the VesselView 702:

- Touchscreen with buttons
- VesselView Link module required
- Mounting options:
 - Flush mount
 - Surface mount
- Wi-Fi capability (requires GoFree Wi-Fi module)
- Internal bluetooth
- Internal GPS (10 Hz)

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

- Supports sonar with additional hardware for compressed high-intensity radiated pulse (CHIRP)
- Full featured chartplotter
- Supports backup camera



61270


VesselView 702

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

VesselView 702 Connections

The following diagram is an example of how the VesselView 702 could be installed.



Typical NMEA communication connection

- a- Chartplotter or multifunction display
- b- 120 ohm termination resistor, male
- c- 120 ohm termination resistor, female
- d- NMEA 2000 fused power source
- e- Power bus
- f- Wi-Fi module
- g- VesselView 702
- h- VesselView Link controller
- i- VesselView Link harness
- j- Junction box

NOTE: The Wi-Fi module is a wireless bridge that adds wireless functionality to compatible multifunction displays which will allow future software updates to be delivered to the VesselView 702 via the Wi-Fi module.

Operational Features

The following descriptions define how the Mercury Diesel with Joystick Piloting for Sterndrive system positions the drives during various operational transitions, depending on the position of the steering wheel.

Key-Up

No action taken; the drives do not move.

Engines Start Up

The drives will steer to a position that will match the steering wheel position (within one revolution) relative to the steering wheel center position.

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

Exiting Joystick

The drives will move to the center position and the steering wheel will take the current position as the new center. To return the steering wheel to its original (true) center, operate the boat normally and the system will gradually align the center position of the drives to the original (true) center of the steering wheel.

Exiting Skyhook

The drives will move to the center position and the steering wheel will take the current position as the new center. To return the steering wheel to its original (true) center, operate the boat normally and the system will gradually align the center position of the drives to the original (true) center of the steering wheel.

Exiting Route or Heading Mode

The drives will not move from their last position without steering input. The steering wheel position will not match the position of the drives, but will steer the boat with any input to the steering wheel. Normal operations of the boat will gradually align the center position of the drives to the original (true) center of the steering wheel.

Rigging Kit Table

NOTE: When rigging a boat with two stations, the main station and second station kits are required.

Application	Main Station Kit Part Number	Second Station Kit Part Number
Dual	8M0115485	8M0116471

Auxiliary Joystick Table

Application	Auxiliary Joystick Part Number
Auxiliary joystick kit (dual engine)	8M0115487

Resistor Pack Table

NOTE: When installing a second or third auxiliary joystick, you must replace the existing resistor pack that is included in the auxiliary joystick kit with one of the following part numbers based on the application.

Resistor Pack Part Numbers	
Resistor pack for second auxiliary joystick	898091T02
Resistor pack for third auxiliary joystick	898091T03

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.

THE INFORMATION IN THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHT AND IS THE PROPERTY OF MERCURY MARINE.

This document is provided for the sole and exclusive use of the original recipient as prescribed by Mercury Marine and may not be distributed or copied, digitally or otherwise, without the prior written consent of Mercury Marine.