

## 300 Pro Max/Magnum Specifications S/N 0G610006 & Up

MODEL	300 PRO MAX/SUPER MAGNUM EFI
Propshaft Horsepower	300 (224 kw)
Displacement	185 cu. in. (3044cc)
Bore	3.63" (92mm)
Bore Type	Cast Iron
Stroke	3.00" (76mm)
Idle RPM (In Forward Gear)	600–700
Maximum W.O.T. RPM	5600–6100 (Rev. Limit At 6350)
Idle Timing	3° ATDC to 1° BTDC
Maximum Spark Advance	26° Non Adjustable
Compression Ratio	10.1:1
Compression Pressure	125 PSI
Fuel Recommendation	92 Octane Minimum (Posted) R+M/2
Oil Recommendation	TCW-3 Premium Plus
Oil Injection	Variable Ratio
Fuel Pressure	39 PSI
Firing Order	1-2-3-4-5-6
Spark Plugs/Gap 0.035 In.	Champion QL77CC
Charging System	60 Amp Belt Driven
Battery Rating	630 Marine Cranking Amps (MCA) or 490 Cold Cranking Amps (CCA)
Transom Height	20" & 25"
Lower Unit Oil Capacity	28.0 fl. oz. (828.0ml)
Recommended Gear Lube	Hi-Performance Gear Lube (92-816026A55)
Gear Ratio	1.62:1 Sport Master 1.75:1 Torque Master & Fleet Master
Rotation	Left or Right Hand (SM) (FM), Right Hand (TM)
Flywheel	Cast Iron
Gear Shift	Forward, Neutral and Reverse
Induction	Fuel Injection
ECU Box	Spark (830044-6) Fuel (830046-3)
Weight	467 lbs. (212 kg)
Warranty	1 Year (Plus 1 Year Q-Guard) Q-Guard Optional